




## FU-BLP-105LX-RGB Series Waterproof Seven-colored Module

FU-BLP-105L3-RGB Series seven-colored combines LED lights of 3 colors-red, green and blue together, and achieves very fantastic lighting effect with varied colors using RGB control system. It is the ideal replacement product for high voltage neon lights, for low voltage neon lights. It is low voltage driven, safe and reliable.


**FU-BLP-105L3-RGB-001**

**FU-BLP-105L6-RGB-001**

**FU-BLP-105L9-RGB-001**


Color	Blue	Red	Green
Quantity of LED lamps	1	1	1
Luminous Flux per Module	4.5 Lm		
Power Consumption	0.3-0.9W		
Working Voltage	12VDC		
Working Current	20~60mA		
Ambient temperature	-20~+60°C		
Storage Temperature	-40~+80°C		
Waterproof Rank	IP68		
External Dimension	30 x 24 x 13mm		
Module Space	100mm		
Weight	17.5g		
Package	100pcs/roll (10m)		

Color	Blue	Red	Green
Quantity of LED lamps	2	2	2
Luminous Flux per Module	6 Lm		
Power Consumption	0.3-0.9W		
Working Voltage	12VDC		
Working Current	20~60mA		
Ambient temperature	-20~+60°C		
Storage Temperature	-40~+80°C		
Waterproof Rank	IP68		
External Dimension	31 x 32 x 11mm		
Module Space	150mm		
Weight	27g		
Package	50pcs/roll (7.5m)		

Color	Blue	Red	Green
Quantity of LED lamps	3	3	3
Luminous Flux per Module	9 Lm		
Power Consumption	0.3-0.9W		
Working Voltage	12VDC		
Working Current	20~60mA		
Ambient temperature	-20~+60°C		
Storage Temperature	-40~+80°C		
Waterproof Rank	IP68		
External Dimension	65 x 60 x 13mm		
Module Space	250mm		
Weight	60g		
Package	25pcs/roll (3.25m)		

Color	Blue	Red	Green
Quantity of LED lamps	3	3	3
Luminous Flux per Module	9 Lm		
Power Consumption	0.3-0.9W		
Working Voltage	12VDC		
Working Current	20~60mA		
Ambient temperature	-20~+60°C		
Storage Temperature	-40~+80°C		
Waterproof Rank	IP68		
External Dimension	65 x 60 x 13mm		
Module Space	250mm		
Weight	60g		
Package	25pcs/roll (3.25m)		

<http://www.ukai.com-ukai@ukai.com>