

Color Range: Daylight White (4000K).

Light Source: SMD 3528 LED

Housing: AL and High Strength PC

Operation Temperature: -20°C to 40°C

Life Span: 50.000 hours-duty cycle

Voltage Range: AC100~277V

Frequency: 50Hz / 60Hz

Beam angle: 120°

PC Lens: Frosted

Color index (CRI): ≥ 80

PF: ≥ 0.93

Power Efficiency: ≥ 0.87

Net Weight: 210g/600mm 368g/1200mm 443g/1500mm



- Aluminium PCB better heat dissipation than FR4
- Isolating driver inside.
- Patented 180Deg rotating end cap design.
- 50.000h expected lifetime.
- Up to 70% energy saving.
- High Color Rendering Index CRI>80.
- Direct retrofit without modification.
- Instant Start.



Introduction

Designed specially for meat displays, it features a pink color which displays the meat at its best

Application

Shopping Mall etc..



RoHS

Parameter

Model	Power(W)	Size(mm)	LEDs(pcs)	Color	Frosted Lens	
					Lumen	Lm/W
KRYLAST-6GX-RSD2	11	26*588	108	4000K	825	75
KRYLAST-9GX-RSD2	17	26*894	168	4000K	1275	75
KRYLAST-12GX-RSD2	20	26*1198	216	4000K	1500	75
KRYLAST-15GX-RSD2	24	26*1498	240	4000K	1800	75